



Swerub RA mountings are used in a wide range of Static and Mobile applications.

### STANDARDIZED DESIGN

Flanged Plate – RA 100, 200, 350, 500, 800

Square Plate – RA 1200, 1800

### APPLICATIONS

- Vehicles, both Industrial and Commercial
- Diesel Engines, Marine Engines
- Construction and Plant Equipment
- Pumps, Compressors, Generators

### CHARACTERISTICS

Rubber profile used in shear and compression to obtain vertical flexibility and horizontal stability providing vibration reduction up to 95% in all directions.

For e.g. 1500 rpm the isolation is approx. 75 - 85%.

Fail Safe Design. Corrosion protected. Contamination protected from Oil and Fuel.

Rubber Hardness options:

A NR40 enabling maximum loads from 105 up to 1300 kg.

B NR60 enabling maximum loads from 200 up to 2100 kg.

Article number	d1 [mm]	H [mm]	a2 [mm]	a1 [mm]	d3 [mm]	d2 [mm]	D [mm]	M-max A NR40	M-max A NR60
RA 100	M10, M12	30	110	130	9	12	79	105	200
RA 200	M10, M12	35	124	150	10	15	94	185	285
RA 350	M12, M16	38	144	175	14	18	101	250	450
RA 500	M16	42	158	192	14	18	123	250	700
RA 800	M16	46	182	216	14	18	144	750	1300
RA 1200	M20	58	140	170	14		161	900	1600
RA 1800	M20	66.5	160	190	14		181	1300	2100

