



T-Slim T-shaped Damper

STANDARDIZED DESIGN

Natural rubber NR

Hardness (default 55 +/-5 Shore A)

Metal insert: ST37 (galvanized, DIN EN 12329 – Fe//Zn12//A)

OPTIONAL DESIGN

Hardness

- 40 +/-5 Shore A
- 55 +/-5 Shore A (default)
- 70 +/-5 Shore A

Metal insert

- ST37 (default, galvanized DIN EN 12329 – Fe//Zn12//A)
- A2 (stainless, AISI 304)
- A4 (stainless, AISI 316)
- MS (brass)

Rubber Qualities

- NR (default)
- CR
- NBR
- EPDM
- VMQ

APPLICATIONS

Swerub TF is used to achieve a flexible and damped connection between two parts. When tightening the screw, the rubber cylinder bulges in order to get a flexible connection.

CHARACTERISTICS

- Operation temperature -40 - +80 °C
- Should not be used at oil, alkaline, acid

TYPE	d1 [mm]	d2 [mm]	d3 [mm]	H [mm]	h1 [mm]
TS1	M3	7.2	9	9	3
TS2	M4	9.3	12	12	3.2
TS3	M5	10.2	15	14.5	3.5
TS4	M6	12.7	18	17	4.3
TS5	M8	16	24	22	5.3

