



T-Thick T-shaped Damper

STANDARDIZED DESIGN

Natural Rubber NR

Hardness (default 60 +/-5 Shore A)

Metal insert: ST37 (galvanized, DIN EN 12329 – Fe//Zn12//A)

OPTIONAL DESIGN

Hardness

- 40 +/-5 Shore A
- 60 +/-5 Shore A (default)
- 70 +/-5 Shore A

Metal insert

- ST37 (default, galvanized DIN EN 12329 – Fe//Zn12//A)
- A2 (stainless, AISI 304)
- A4 (stainless, AISI 316)

APPLICATIONS

Perfect for absorbing vibration generated by pumps, fans, washing machines, electric engines, control cabinets and other industrial and agricultural equipments.

CHARACTERISTICS

- Elastomer (default natural rubber, NK)
- Operation temperature -40 - +80 °C
- Should not be used at oil, alkaline, acid

TYPE	d1 [mm]	d2 [mm]	d3 [mm]	h1 [mm]	H [mm]
TT1	27.7	20	10	5.6	17.5
TT2	44.5	31.5	13	10.4	25.4
TT3	50.8	34.3	13	13.5	35
TT4	63.5	41	16	15.7	44.5
TT5	64	38	16	16	23
TT6	95	56.6	20	25.4	50.8

