



Wall-Ceiling Mounting – Lower
Wall-Ceiling Mounting – Upper

SWERUB WCM mountings are used for isolating vibrations from wall- or ceiling mounted equipment.

STANDARDIZED DESIGN

Natural rubber NR
Hardness 60 +/-5 Shore A

OPTIONAL DESIGN

Hardness

- 40 +/-5 Shore A
- 60 +/-5 Shore A (default)

METAL CHARACTERISTICS

Metal insert: ST37 (galvanized,
DIN EN 12329 – Fe//Zn12//A)

APPLICATIONS

Isolation of vibrations from wall-mounted equipment and machinery. Also suitable for Ceiling-mounted equipment and machinery.

CHARACTERISTICS

Operation temperature -40 - +80 °C
Should not be used together with oil, alkaline, acid

Article number	E [mm]	K [mm]	A [mm]	H [mm]	d [mm]	N [mm]	t [mm]	G [mm]	M-Max- (kg) 40°Shore	M-Max- (kg) 60°Shore	F-Max- (kg) 40°Shore	F-Max- (kg) 60°Shore
WCM-U	75	114	96	33	9	15	2.5	M8	14	25	30	70
WCM-L	75	114	96	33	9	15	2.5	M8	14	25	30	70

TYPE WCM

